

# Steel Reinforced High Pressure

## Çelik Tel Örgülü Yüksek Basınç Dayanımlı



	TUBE	: HYDRAULIC OILS, AIR AND WATER BASED FLUIDS RESISTANT POLYESTER.
	REINFORCEMENT	: HIGH TENSILE STEEL WIRE BRAID.
	COVER	: OIL, ABRASION AND WEATHER RESISTANT POLYURETHANE.
	APPLICATION	: FOR VERY HIGH PRESSURE HYDRAULIC SYSTEMS USED IN VARIOUS INDUSTRIES AND AGRICULTURE.
	FITTINGS	: PRESSED.

	SEELE	: BESTÄNDIGER POLYESTER GEGEN HYDRAULIKÖL, LUFT UND WASSER ENTHALTENDE FLÜSSIGKEITEN.
	EINLAGEN	: HOCH REISSFESTES STAHLDRAHTGEFLECHT.
	DECKE	: ÖL- UND WETTERBESTÄNDIGES, ABRIEBFESTES POLYURETHAN.
	ANWENDUNG	: GEEIGNET ALS HYDRAULIKSCHLAUCH FÜR LANDWIRTSCHAFT UND BAUMASCHINEN MIT HOHEM ARBEITSDRUCK.
	EINBAND	: PRESSARMATUR.

	SOTTOSTRATO	: POLIESTERE RESISTENTE AGLI OLII IDRAULICI E FLUIDI A BASE ACQUOSA ED ARIA.
	RINFORZO	: TRECCA IN ACCIAIO AD ALTA TENACITÀ.
	COPERTURA	: IN POLIURETANO ANTIABRASIONE, RESISTENTE ALL'OLIO ED AGLI AGENTI ATMOSFERICI.
	IMPIEGO	: PER SISTEMI IDRAULICI AD ALTA PRESSIONE IN AGRICOLTURA ED INDUSTRIE.
	RACCORDI	: PRESSATI.

	ALT KAT	: HİDROLİK YAĞLARA, HAVA VE SU BAZLI AKIŞKANLARA DAYANIKLI POLYESTER.
	TAKVİYE	: YÜKSEK MUKAVEMETLİ ÇELİK TEL ÖRGÜ.
	ÜST KAT	: YAĞ, AŞINMA VE HAVA ŞARTLARINA DAYANIKLI POLIÜRETAN.
	KULLANIM YERİ	: YÜKSEK BASINÇ GEREKTİREN ENDÜSTRİYEL VE TARIMSAL HİDROLİK SİSTEMLER.
	RAKORLAMA	: SIKMA.

ID/iç		OD/DÇ		WP/ÇB		BP/PB		BR/KY/r		W/A		L/B	
inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m	m			
1/8"	3.2	8.2	325	4713	1300	18850	30	110	+10				
5/32"	4.1	9	300	4350	1200	17400	30	113	+10				
3/16"	5	9.5	293	4249	1172	16994	35	130	+10				
1/4"	6.5	12	287	4162	1148	16646	40	170	+10				
5/16"	8	13	217	3147	868	12586	50	167	+10				
3/8"	9.7	15.5	212	3074	848	12296	60	240	+10				
1/2"	13	18.6	185	2683	740	10730	80	286	+10				
5/8"	16.5	22.5	150	2175	600	8700	120	384	+10				
3/4"	19.5	25.7	125	1813	500	7250	160	423	+10				
1"	25	31.5	100	1450	400	5800	200	496	+10				



-40 °C / +100 °C  
-40 °F / +212 °F

(For transfer of water based fluids and air max +65 °C / 149 °F)

(Beim Transport von Wasser und Luft enthaltenden Flüssigkeiten max. 65 °C / 149 °F)

(Per conduzione di fluidi a base acquosa ed aria max +65 °C / 149 °F)

(İçinden geçen hava ve su bazlı akışkanlar için en yüksek +65 °C / 149 °F)

Possible applications:

Anwendungsbeispiele:

Esempi d' applicazione:

Bazı kullanım yeri örnekleri:



NORMS  
NORMEN  
NORME  
NORMLAR

MARKING  
BESCHRIFTUNG  
MARCATURA  
MARKALAMA

INK JET

COLOUR  
FARBEN  
COLORI  
RENKLER

