

Textile (Aramid) Braided High Pressure Twin

Tekstil (Aramid) Örgülü Yüksek Basınç Dayanımlı İkiz



TUBE : HYDRAULIC OILS, AIR AND WATER BASED FLUIDS RESISTANT POLYESTER.
REINFORCEMENT : VERY HIGH TENSILE ARAMIDIC FIBER BRAID.
COVER : OIL, ABRASION AND WEATHER RESISTANT POLYURETHANE.
APPLICATION : FOR AIR, WATER, MINERAL AND/OR SYNTHETIC OILS DISCHARGE AT HIGH PRESSURE.
FITTINGS : PRESSED OR REUSABLE.



SEELE : BESTÄNDIGER POLYESTER GEGEN HYDRAULIKÖL, LUFT UND WASSER ENTHALTENDE FLÜSSIGKEITEN.
EINLAGEN : HOCH REISSFESTES ARAMIDGEFLECHT.
DECKE : ÖL- UND WETTERBESTÄNDIGES, ABRIEFESTES POLYURETHAN.
ANWENDUNG : GEEIGNET FÜR TRANSPORT VON LUFT, WASSER UND/ODER HYDRAULIKÖLEN BEI HOHEM ARBEITSDRUCK.
EINBAND : PRESSARMATUR ODER SCHRAUBARMATUR.



SOTTOSTRATO : POLIESTERE RESISTENTE AGLI OLII IDRAULICI E FLUIDI A BASE ACQUOSA ED ARIA.
RINFORZO : TRECCA IN FIBRA ARAMIDICA AD ALTISSIMA TENACITÀ.
COPERTURA : IN POLIURETANO ANTIABRASIONE, RESISTENTE ALL'OLIO ED AGLI AGENTI ATMOSFERICI.
IMPIEGO : PER MANDATA DI ARIA, ACQUA, OLII MINERALI E/O SINTETICI AD ALTISSIMA PRESSIONE.
RACCORDI : PRESSATI O RECUPERABILI.



ALT KAT : HİDROLİK YAĞLARA, HAVA VE SU BAZLI AKIŞKANLARA DAYANIKLI POLYESTER.
TAKVİYE : YÜKSEK MUKAVEMETLİ TEK KAT ARAMİD ÖRGÜ.
ÜST KAT : YAĞ, AŞINMA VE HAVA ŞARTLARINA DAYANIKLI POLİÜRETAN.
KULLANIM YERİ : YÜKSEK BASINÇ DAYANIMI GEREKTİREN, HAVA, SU MİNERAL VE/VEYA HİDROLİK YAĞLARIN TAHLİYE İŞLERİNDE.
RAKORLAMA : SIKMA VEYA VİDALI.

									
ID/iç		OD/Dış	WP/ÇB		BP/PB		BR/KY/r	W/A	L/B
inch	mm	mm	bar	psi	bar	psi	mm	g/m	m
1/8"	3.2	7.5	300	4350	1200	17400	25	46	+10
5/32"	4.1	8.2	300	4350	1200	17400	30	52	+10
3/16"	5	8.5	250	3625	1000	14500	35	48	+10
1/4"	6.5	11.4	225	3263	900	13050	40	82	+10
5/16"	8	13	200	2900	800	11600	55	92	+10
3/8"	9.7	15	190	2755	760	11020	75	102	+10
1/2"	13	18.6	175	2538	700	10150	85	136	+10
5/8"	16.5	22.5	150	2175	600	8700	110	217	+10
3/4"	19.5	25.5	130	1885	520	7540	140	245	+10
1"	25	32	100	1450	400	5800	180	363	+10



-40°C / +100°C
-40°F / +212°F

(For transfer of water based fluids and air max +65 °C / 149 °F)
(Beim Transport von Wasser und Luft enthaltenden Flüssigkeiten max. 65 °C / 149 °F)
(Per conduzione di fluidi a base acquosa ed aria max +65 °C / 149 °F)
(İçinden geçen hava ve su bazlı akışkanlar için en yüksek +65 °C / 149 °F)

Possible applications: Anwendungsbeispiele: Esempi d' applicazione: Bazı kullanım yeri örnekleri:



NORMS NORMEN NORME NORMLAR		MARKING BESCHRIFTUNG MARCATURA MARKALAMA	INK JET	COLOUR FARBEN COLORI RENKLER	
-------------------------------------	--	---	---------	---------------------------------------	--