

# PRO™ SERIES HYDRAULIC HOSE



## PRO1T



↔		○		⌚		🌀		👤		🏋️		📏
-size	DN	"	"	mm	PSI	MPa	PSI	MPa	mm	kg/100m	REF.	
-4	6	1/4	0.49	12.5	3250	22.5	13000	90.0	75	19	4PRO1T	
-5	8	5/16	0.54	13.6	3100	21.5	12400	86.0	85	21	5PRO1T	
-6	10	3/8	0.62	15.8	2600	18.0	10400	72.0	90	28	6PRO1T	
-8	12	1/2	0.75	19.0	2325	16.0	9300	64.0	130	34	8PRO1T	
-10	16	5/8	0.89	22.5	1900	13.0	7600	52.0	150	43	10PRO1T	
-12	19	3/4	1.02	25.9	1525	10.5	6100	42.0	180	50	12PRO1T	
-16	25	1	1.31	33.4	1275	8.8	5100	35.2	230	82	16PRO1T	

<b>RECOMMENDED FOR</b>	High pressure hydraulic application. Easy to route and install in tight areas.
<b>TUBE</b>	NBR (Nitrile) based.
<b>REINFORCEMENT</b>	One braid of high-tensile steel wire.
<b>COVER</b>	SBR (Styrene-Butadiene) based. MSHA approved.
<b>TEMPERATURE RANGE</b>	-40°C to +100°C. For water emulsions, etc. see Engineering and technical data page 292.
<b>STANDARDS</b>	EN 857 1SC. ISO 11237 1SC.
<b>COUPLINGS</b>	EX.